

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/076791 A1

(51) International Patent Classification⁷: F02M 35/024

(21) International Application Number: PCT/IB02/03574

(22) International Filing Date:
4 September 2002 (04.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
P00200200120 8 March 2002 (08.03.2002) ID

(71) Applicant and

(72) Inventor: WIJAYA, Heru, Prasanta [ID/ID]; Graha
Famili D.183, PR. Kali Kendal, Surabaya 60226 (ID).

(74) Agent: PRIAPANTJA, Cita, Citrawinda; Biro Oktroi
Roosseno, Kantor Taman A-9, Unit C1 - C2, Jl. Mega
Kuningan, Kuningan, Jakarta 12950 (ID).

(81) Designated States (*national*): AU, BR, CA, CN, IN, JP,
KR, MX, NZ, PH, SG, US, VN.


(84) Designated States (*regional*): Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE, SK, TR).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: KNOCKED-DOWN AIR FILTER FOR INTERNAL COMBUSTION ENGINE



(57) Abstract: Efficiency leading to saving in transportation is a must at this competitive era. The choice of an automotive vehicle as a transportation means in mining, plantation, and forestry entails a special tactics in order to minimize the operational, maintenance and replacement cost of the air filter used in its internal combustion engines, especially the air filter whose entire parts should be replaced when its clogged filtering medium (7) is replaced. The air filter presently invented is a knocked-down air filter, i.e., an air filter whose part that should be replaced is its filtering medium (7) and inner mesh (6) only which are bound together by lower rubber (5) and upper rubber (8). Its other parts such as lower housing (1), upper housing (9), perforated plate (3) and reinforcing pile (4) are not necessarily replaced. A manually opened and closed locker (11) unite this knocked-down air filter as a single unit.

WO 03/076791 A1

DT09 Rec'd PCT/PTO 01 SEP 2004

Description

KNOCKED-DOWN AIR FILTER FOR INTERNAL COMBUSTION ENGINE

5 Field of The Invention

This invention relates to an air filter for an automotive engine.

10 Background of The Invention

Vehicles play an important role in economy especially as the means of transportation for goods and personnel. Of them, trucks and buses are of the most importance in connection with this invention. These vehicles adopt internal combustion engine for operation.

The choice of automotive vehicles as a transportation means entails a specified strategy in order to minimize the operational and maintenance cost.

20 Industries such as mining, plantation, and forestry are other examples of fields in which this invention is applied. The most frequently used vehicles in the those fields are dump trucks, excavators, forklifts and multiple-wheeled trucks.

25 There are still a lot of industrial machines and electrical generators that use internal combustion engine for their operation.

30 One of the internal combustion engine components that needs maintenance and periodic replacement is air filter. This air filter must be periodically be replaced in order to make the fresh air needed for the efficient combustion in the engine keep existing there.

35 The use of this knocked-down air filter in an internal combustion engine will save a lot of money because its part only that should be periodically replaced for an efficient combustion in the engine.

Brief Description of The Invention

Object of this invention is an air filter which can be
5 knocked-down for the reduction of maintenance and replacement
cost in an internal combustion engine.

Air filter of current use (Figure 1) generally comprises
lower housing plate (1) portion, filtering medium (7),
perforated plates (3), and inner mesh (6) assembled as a unit
10 by lower rubber (5) and upper rubber (8) acting, too, as a
binder. For this kind of air filter, all of its components
should be replaced when we replace the air filter.

The preferred embodiment of this invention (Figure 2)
comprises a lower housing (1) as a base, perforated plate (3)
15 hooked to a holding ring (2) at the lower part thereof and
bound to an upper reinforcing ring (10) at the upper part
thereof. The perforated plate (3) acts as a reinforcing means
for the air filter construction and as a retaining means for
filter housing (9) on the upper part of the air filter. To
20 make the air filter more compact in construction, there is
provided on its internal parts a reinforcing pile (4) whose
upper part is bound to the upper reinforcing rings (10) and
lower part is bound to the lower reinforcing ring (2).

Filtering medium (7) is generally folded longitudinally
25 upward whilst inner mesh (6) is engaged with lower rubber (5)
and upper rubber (8). The unification into a single unit of
the filtering medium (7) and the inner mesh (6) with the lower
rubber (5) and the upper rubber (8) form a cylinder which can
be separated individually from this air filter (Figure 3). It
30 is the single unit formed by the filtering medium (7) and the
inner mesh (6) that should only be replaced, not all parts of
the air filter.

For arrangement purpose, lower housing (1), perforated
plate (3), reinforcing pile (4), upper reinforcing ring
35 portion which can be opened for the insertion of the filtering

medium (7), and upper housing plate, are unified with manually opened and closed locker (11). To avoid leakage, a seal (12) can be provided on this air filter engine when the air filter is attached on the combustion engine. Because the part that should be replaced is merely the filtering medium (7) which has been integrally bound with the inner mesh (6) by the lower rubber (5) and the upper rubber (8), the use of this invention will save a lot of money.

10 Brief Description of The Drawing

Figure 1 is a traversed cross-section of the half of the air filter currently used.

Figure 2 is a traversed cross-section of the half of the preferred embodiment of the air filter presently invented.

Figure 3 is a traversed cross-section of the half of the filter medium.

Figure 4 is a traversed cross-section of the half of the presently-invented knocked-down air filter in detached condition.

Figure 5 is the traversed cross-section of the half of varied locking model.

Figure 6 is a traversed cross-section of the half of the presently-invented knocked-down air filter with varied locking model using hook system.

Detailed Description of The Invention

The subject of this invention is an air filter which can be knocked-down in order to reduce maintenance and replacement costs in an internal combustion engine.

Air filter of current use (Figure 1) generally comprises lower housing plate (1) portion, filtering medium (7) which can be upwardly folded, perforated plates (3), and inner mesh (6) formed as a cylinder and bound into an individual unit by

the lower rubber (5) and upper rubber (8) which acts too as a binder. With such a configuration, it is merely the filtering medium itself that should be replaced, not the whole parts of the air filter.

5 Part of an air filter that should be replaced is actually the filtering medium only. This medium, when clogged, causes the fresh air unable to enter the combustion chamber of an internal combustion engine.

10 Based on this consideration, it is developed an economic knocked-down air filter where only its filtering medium (7) and inner mesh (6) that should be periodically replaced. Inner mesh (6) provided as a means of maintaining The shape of the filtering medium is maintained by inner mesh (6) which is defined by upwardly extending longitudinal folds.

15 The preferred embodiment of this invention (Figure 2) comprises a lower housing (1) as a base, perforated plate (3) hooked to a holding ring (2) at its lower part and bound to an upper reinforcing ring (10) at its upper part. Perforated plate (3) function as a reinforcing means for the air filter construction and as a retaining means for filter housing (9) on the upper part of the air filter. To make the air filter more compact in construction, there is provided on its internal parts a reinforcing pile (4) whose upper part is bound to the upper reinforcing rings (10) and lower part is bound to the lower reinforcing ring (2).

20 Filtering medium (7) is generally folded longitudinally upward whilst inner mesh (6) is engaged with lower rubber (5) and upper rubber (8). The unification into a single unit of the filtering medium (7) and the inner mesh (6) with the lower rubber (5) and the upper rubber (8) form a cylinder which can be separated individually from this air filter (Figure 3). It is the single unit formed by the filtering medium (7) and the inner mesh (6) that should only be replaced, not all parts of the air filter.

30 In arranging the air filter, lower housing (1),

perforated plate (3), reinforcing pile (4), upper reinforcing ring portion which can be opened for the insertion of the filtering medium (7), and upper housing plate, are unified with manually opened and closed locker (11). To avoid leakage,
5 a seal (12) is provided on this air filter engine when the air filter is attached on the combustion engine.

Because the part that should be replaced is merely the filtering medium (7) which has been integrally bound with the inner mesh (6) by the lower rubber (5) and the upper rubber
10 (8), the use of this invention will save a lot of money. Parts of the presently invented air filter, i.e., air filter that can be knocked down, can be seen in Figure 4.

For people skilled in the art, various modifications of the preferred embodiment are allowed as long as they do not
15 depart from the spirit of the invention.

One of these modifications is the shape of the locker (11). This locker (11) should be bound on perforated plate (3), on lower housing (1), or on upper housing (9). It can also be clamped on one parts of the air filter instead of
20 being bound on it (Figure 5). Another characteristic that can be modified is the arrangement of the partial binding of the knocked down parts of the air filter. Figure 6 shows a modified locking model of the lower housing (1) and the upper housing (9). The hook used for this modification can be a
25 thread of a screw.

The shape of the reinforcing pile is also subject to modification, in which it can be as a spiral. Perforated plate can be replaced by reinforcing spiral or pile. Inner mesh (6) can be provided or not on the filtering medium. When provided,
30 it can be separately made or replaced by spiral or pile. Longitudinal folds that form a filtering medium can also be made from polymeric material. A filtering medium without folds is also possible.

Claims

1. Knocked-down air filter for internal combustion engine characterized by
5 parts of a filtering medium (7) and inner mesh (6) engaged by lower rubber (5) and upper rubber (8) acting as a binder so that filtering medium (7) and inner mesh (6) engaged integrally;
detachable lower housing (1), perforated plate (3),
10 reinforcing pile (4) and upper housing (9) which can be assembled, where parts of a filtering medium (7) and inner mesh (6) which have been engaged can be integrally formed into an air filter when combined with lower housing (1), perforated plate (3), reinforcing pile (4),
15 and upper housing (9) by means of locker (11).
2. Knocked-down air filter for internal combustion engine defined in claim 1 in which the binding between lower housing (1) and upper housing (9) is effected by a
20 perforated plate (3) by means of a hook-locking system.
3. Knocked-down air filter for internal combustion engine defined in claim 1 applying a clip-locking system.
- 25 4. Knocked-down air filter for internal combustion engine defined in claim 1 in which the binding between lower housing (1) and upper housing (9) is effected by a perforated plate (3) by means of a thread-locking system.
- 30 5. Knocked-down air filter for internal combustion engine defined in claim 1 with a reinforcing means in the form of a spiral.
- 35 6. Knocked-down air filter for internal combustion engine characterized by

parts of a filtering medium (7) and inner mesh (6) equipped with lower rubber (5) and upper rubber (8) which functions as a binder as well as stabilizer for the filtering medium (7) and its consistent shape;

5 detachable lower housing (1), perforated plate (3), inner mesh (6) and upper housing (9):
where parts of a filtering medium (7), lower housing (1), perforated plate (3), inner mesh (6) and upper housing (9) can be assembled into an air filter by means of
10 locker (11).

7. Filtering medium (7) constituted by a plurality of upwardly extending folds made from filtering paper or other substances where rubbers are attached on upper and
15 lower parts thereof in order to stabilize the shape of the filtering medium.

8. Knocked-down air filter for internal combustion engine disclosed in claim 6 in which the engagement model
20 between lower housing (1) and upper housing (9) is effected by a perforated plate (3) and an inner mesh (6) using hook, clip and thread-locking systems.

9. Knocked-down air filter for internal combustion engine defined in claim 1 and claim 6 whose lower housing (1) and upper housing (9) are engaged by a reinforcing means
25 in the form of spiral or pile.

30

35

AMENDED CLAIMS

[received by the International Bureau on 23 April 2003 (23.04.03);
original claims 1-9 replaced by new claims 1-10 (2 pages)]

1. Knocked-down air filter for internal combustion engine
characterized by
5 parts of a filtering medium (7) and inner mesh (6)
engaged by lower rubber (5) and upper rubber (8) acting
as a binder so that filtering medium (7) and inner mesh
(6) engaged integrally;
detachable lower housing (1), perforated plate (3),
10 reinforcing pile (4) and upper housing (9) which can be
assembled, where parts of a filtering medium (7) and
inner mesh (6) which have been engaged can be integrally
formed into an air filter when combined with lower
housing (1), perforated plate (3), reinforcing pile (4),
15 and upper housing (9) by means of locker (11).
2. Knocked-down air filter for internal combustion engine
defined in claim 1 in which the binding between lower
housing (1) and upper housing (9) is effected by a
20 perforated plate (3) by means of a hook-locking system.
3. Knocked-down air filter for internal combustion engine
defined in claim 1 applying a clip-locking system.
- 25 4. Knocked-down air filter for internal combustion engine
defined in claim 1 in which the binding between lower
housing (1) and upper housing (9) is effected by a
perforated plate (3) by means of thread-locking system.
- 30 5. Knocked-down air filter for internal combustion engine
defined in claim 1 with a reinforcing means in the form
of a spiral.
6. Knocked-down air filter for internal combustion engine
35 characterized by

parts of a filtering medium (7) and inner mesh(6) equipped with lower rubber(5) and upper rubber(8) which functions as a binder as well as stabilizer for the filtering medium (7) and its consistent shape;

5 detachable lower housing (1), perforated plate (3), inner mesh (6) and upper housing (9); where parts of a filtering medium(7), lower housing(1), perforated plate (3), inner mesh (6) and upper housing (9) can be assembled into an air filter by means of
10 locker (11).

7. Filtering medium (7) constituted by a plurality of upwardly extending folds made from filtering paper or other substances where rubbers are attached on upper
15 and lower parts thereof in order to stabilize the shape of the filtering medium.

8. Knocked-down air filter for internal combustion engine disclosed in claim 6 in which the engagement model
20 between lower housing (1) and upper housing (9) is effected by a perforated plate (3) and an inner mesh(6) using hook, clip and thread-locking systems.

9. Knocked-down air filter for internal combustion engine defined in claim 1 and claim 6 whose lower housing (1)
25 and upper housing (9) are engaged by a reinforcing means in the form of spiral or pile.

10. Knocked-down air filter for internal combustion engine defined in claim 6 where the folded body of the
30 filtering medium is provided with a plastic reinforcing substance wound as a ring around the filtering medium.

35




Figure 1

10/506394




Figure 2

SUBSTITUTE SHEET (RULE 26)




Figure 3




Figure 4




Figure 5.
SUBSTITUTE SHEET (RULE 26)




Figure 6

INTERNATIONAL SEARCH REPORT

PCT/12/03574

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F02M35/024

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHEDMinimum documentation searched (classification system followed by classification symbols)
IPC 7 F02M B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2001/000845 A1 (COULONVAUX PAUL R) 10 May 2001 (2001-05-10) page 2, paragraphs 13-15; figure 2 ---	1,3,6,7
X	US 4 720 292 A (ENGEL DONALD F ET AL) 19 January 1988 (1988-01-19) column 2, line 46 -column 4, line 55; figure 1 ---	1,3,6,7
A	US 6 159 261 A (BINDER WALTER ET AL) 12 December 2000 (2000-12-12) column 3, line 46 -column 4, line 25; figure 3 ---	1
A	US 6 022 055 A (COULONVAUX PAUL R ET AL) 8 February 2000 (2000-02-08) abstract -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.*** Special categories of cited documents:**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

9 December 2002

Date of mailing of the international search report

19/12/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pileri, P

INTERNATIONAL SEARCH REPORT

PCT/IB 02/03574

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001000845 A1	10-05-2001	US 6187240 B1	13-02-2001
		US 5863313 A	26-01-1999
		US 5693109 A	02-12-1997
		US 5547480 A	20-08-1996
		AU 692514 B2	11-06-1998
		AU 1561595 A	08-08-1995
		BR 9506629 A	16-09-1997
		CA 2181577 A1	27-07-1995
		CN 1139884 A , B	08-01-1997
		DE 29521172 U1	13-03-1997
		DE 69513145 D1	09-12-1999
		DE 69513145 T2	25-05-2000
		EP 0740574 A1	06-11-1996
		ES 2141331 T3	16-03-2000
		FI 962885 A	11-09-1996
		HK 1013968 A1	29-09-2000
		JP 9508850 T	09-09-1997
		WO 9519832 A1	27-07-1995
		ZA 9500456 A	22-07-1996
US 4720292 A	19-01-1988	CA 1340177 A1	08-12-1998
		WO 8901818 A1	09-03-1989
		ZA 8706699 A	25-05-1988
		AU 610837 B2	30-05-1991
		AU 7969887 A	31-03-1989
		BR 8707863 A	01-03-1990
		DE 3751225 D1	11-05-1995
		DE 3751225 T2	02-11-1995
		EP 0329659 A1	30-08-1989
		JP 2501201 T	26-04-1990
		JP 2605072 B2	30-04-1997
		KR 9512519 B1	18-10-1995
US 6159261 A	12-12-2000	DE 19634720 A1	05-03-1998
		BR 9711282 A	17-08-1999
		DE 59703979 D1	09-08-2001
		WO 9808589 A1	05-03-1998
		EP 0958032 A1	24-11-1999
		ES 2160945 T3	16-11-2001
		JP 2000516850 T	19-12-2000
		ZA 9707212 A	20-02-1998
US 6022055 A	08-02-2000	AU 715389 B2	03-02-2000
		AU 5162898 A	03-06-1998
		BR 9714637 A	23-05-2000
		CN 1237232 A	01-12-1999
		EP 0937208 A1	25-08-1999
		JP 2001508527 T	26-06-2001
		KR 2000053285 A	25-08-2000
		PL 333239 A1	22-11-1999
		WO 9821492 A1	22-05-1998
		ZA 9710129 A	11-05-1999